

**TITLE OF THE INVENTION**

Methods of Making Slide-Zippered Reclosable Packages on Horizontal Form-Fill-Seal

5 Machines

**BACKGROUND OF THE INVENTION**

1. Field of the Invention

The present invention relates to the field of reclosable packaging. More particularly,  
10 the present invention relates to methods of making reclosable packages having slide zippers  
on horizontal form-fill-seal (HFFS) machines.

2. Description of the Prior Art

Methods of making reclosable packages on various types of HFFS machines are well-  
15 known in the reclosable packaging art, such as that disclosed in U.S. Patent No. 4,876,842.  
Slide zippers, i.e., plastic zippers opened and closed by a slider, are likewise well-known in  
the reclosable packaging art. Examples of several types of slide zippers can be found in U.S.  
Patent Nos. 5,007,143, 5,008,971, 5,131,121 and 5,664,299.

The reclosable packaging art, however, is virtually, if not totally, silent as it relates to  
20 the manufacture of slide-zippered packages on HFFS machines. Because of the facility  
which is provided by slide zippers to consumers of reclosable packages and because of the  
large volume of reclosable packages made on HFFS machines today, it is highly desirable  
and advantageous to combine the two technologies so that slide-zippered reclosable packages  
can be made on HFFS machines.

## SUMMARY OF THE INVENTION

Accordingly, the object of the present invention is to provide methods of making slide-zippered reclosable packages on HFFS machines.

According to a first embodiment of the present invention, a chain of packages is formed, filled and sealed on an HFFS machine or the like. A pair of opposing film extensions are provided on each package. As the chain of packages is indexed forwardly, a reclosable zipper is inserted between the film extensions of the leading package and sealed thereto. A slider is then inserted on to the reclosable zipper of the leading package and the completed leading package is cut from the chain.

According to a second embodiment of the present invention, packages having reclosable zippers are output from an HFFS machine or the like, either individually or in a chain. A slider is then inserted on to the zipper of each package in turn.

According to a third embodiment of the present invention, packages are formed, filled and sealed on an HFFS machine or the like. During package formation, a reclosable zipper is sealed to each package and then a slider is inserted on to the zipper.

According to a fourth embodiment of the present invention, packages are formed, filled and sealed on a horizontal form-vertical fill-seal (HVFS) machine or the like. During package formation, a reclosable zipper is sealed to each package and a slider is inserted on to each zipper, either before or after zipper sealing.

The present invention will now be described in detail, with frequent reference being made to the drawings identified below in which the same numerals represent the same elements.

## BRIEF DESCRIPTION OF THE DRAWINGS

In the accompanying drawings:

Figure 1 shows packages being made on an HFFS machine in accordance with a first embodiment of the present invention;

5        Figure 2 is a perspective view of a package made on the HFFS machine of figure 1 prior to attaching the zipper;

Figure 3 is a cross-sectional view of the HFFS machine of figure 1 at the slider insertion point;

Figure 4 is a cross-sectional view of a first variation of the HFFS machine of figure 1;

10        Figure 5 shows sliders being inserted on a chain of packages in accordance with a second embodiment of the present invention;

Figure 6 shows sliders being inserted on to individual packages in accordance with a variation of the second embodiment of the present invention;

15        Figure 7 shows packages being made on an HFFS machine in accordance with a third embodiment of the present invention;

Figure 7a is a cross-sectional view of the HFFS machine of figure 7 at the first zipper sealing station;

Figure 8 is a cross-sectional view of the HFFS machine of figure 7;

20        Figure 9 is a cross-sectional view of a package made on the HFFS machine of figure 7;

Figure 10 shows packages being made on an HFFS machine in accordance with a variation of the third embodiment of the present invention;

Figure 11 is a cross-sectional view of packages being made on the HFFS machine of figure 10;

Figure 12 shows packages being made on an HFVS machine in accordance with a fourth embodiment of the present invention;

5 Figure 13 shows packages being made on an HFVS machine in accordance with a first variation of the fourth embodiment of the present invention;

Figure 14 shows packages being made on an HFVS machine in accordance with a second variation of the fourth embodiment of the present invention;

10 Figure 15 is a cross-sectional view of reclosable zipper being sealed to one package side in the HFVS machine of figure 14;

Figure 16 is a cross-sectional view of a package prior to being filled on the HFVS machine of figure 14;

Figure 17 is a cross-sectional view of a tamper evident sealed being placed on a package made on the HFVS machine of Fig. 14;

15 Figure 18 shows packages being made on an HFVS machine in accordance with a third variation of the fourth embodiment of the present invention; and

Figure 19 is a cross-sectional view of a package being formed on the HFVS machine of figure 18.

## 20 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

In accordance with a first embodiment of the present invention, figure 1 shows how slide-zippered packages can be made on a typical thermoform HFFS machine 10. Forming

film 12 is indexed off a coil 14 of the same in a package forming direction. Downstream of the forming film coil 14 at a forming station 15 the forming film 12 is thermoformed, using techniques well-known to those of ordinary skill in the reclosable packaging art, into a chain 13 of advancing box-like bottom portions or trays 16 of what will ultimately be completed packages. Product may then be loaded into the bottom portions 16 at a loading station 17 if desired. After optional product loading, top film 18 is indexed off a coil 20 of the same in the package forming direction, laid over the advancing bottom portions 16 and perimetrically sealed thereto at four locations 22, 24, 26, 28 at a sealing station 21 to form a sealed package 29, as shown in figure 2. The seal at the package opening 22 takes the form of a peel seal so that the consumer can easily gain access to the contents of the package.

As shown in figure 2, which is a perspective view of a sealed package 29 formed on the thermoform HFFS machine of figure 1 prior to zipper and slider insertion, the bottom portion 16 and top film 18 are each provided with film extensions 30, 32 which extend beyond the peel seal 22 on one side of the package 29. The film extensions 30, 32 are not sealed to each other and may readily be spread apart from each other.

After the top film 18 is sealed to the bottom portion 16 at the sealing station 21, the package chain 13 enters a zipper and slider insertion and attaching station 34. At this station 34 the film extensions 30, 32 of the leading package are spread apart from each other and interlocked reclosable zipper 36 supplied from a coil 38 of the same is fed between the film extensions 30, 32, as shown in figure 3, which is a cross-sectional view of the package chain and zipper and slider insertion and attaching station 34. The zipper is comprised of two interlocking closure elements 39, 41 and flanges 40, 42 extending therefrom which are sealed

to the film extensions 30, 32, such as by a pair of seal bars (not shown). After the zipper 36 is thus sealed to the film extensions of the leading package, the zipper 36 is stomped at each end of the package by a stomping apparatus (not shown) to provide end stops for the slider and to ensure that the ends of the zipper 36 do not come apart during use.

5 A slider 44 is then removed from a coil 46 thereof and inserted on to the zipper 36 by a slider insertion apparatus (not shown). The slider and zipper are designed such that the slider will open the zipper as the slider is moved along the zipper in an opening direction towards an opening end of the zipper and close the zipper as the slider is moved along the zipper in a closing direction towards a closing end of the zipper. It is preferable during slider  
10 insertion that the slider be inserted at the closing end of the zipper since the zipper is initially interlocked. The slider will thus be positioned for normal functioning. If the slider is inserted at a location other than at the closing end, it will be necessary to actuate the slider by moving it to the closing end, after which the slider will be in position for normal functioning. Such actuation may be done on the HFFS machine, or it may be done by the initial package  
15 user.

After slider insertion, the leading package is cross-cut from the remainder of the chain 13 by any one of many commonly known cutting apparatuses (not shown) to remove a completed package 48 having a slide zipper.

In practice, the package chain 13 may be a single chain as shown in figure 3, or,  
20 alternatively, may be a multiple chain, such as the double chain 50 shown in cross-section in figure 4. In the case of a double chain, where two packages are joined side by side, the process of making the packages is virtually identical to that described above, except that the

zippers and sliders are attached to the opposite sides 47, 49 of the package chain simultaneously, as shown in figure 4, thus requiring two zipper and slider insertion and attaching stations 34. Additionally, a second cut is needed in the machine direction along the central axis 51 of the chain to remove the side-by-side packages from one another.

5       The foregoing embodiment of the present invention is not limited to practice on thermoform HFFS machines, but may be practiced on any type of package making machine where the packages are formed with film extensions 30, 32 of the type discussed above.

FIG. 5  
FIG. 6  
FIG. 7  
FIG. 8  
FIG. 9  
FIG. 10  
FIG. 11  
FIG. 12  
FIG. 13  
FIG. 14  
FIG. 15  
FIG. 16  
FIG. 17  
FIG. 18  
FIG. 19  
FIG. 20  
FIG. 21  
FIG. 22  
FIG. 23  
FIG. 24  
FIG. 25  
FIG. 26  
FIG. 27  
FIG. 28  
FIG. 29  
FIG. 30  
FIG. 31  
FIG. 32  
FIG. 33  
FIG. 34  
FIG. 35  
FIG. 36  
FIG. 37  
FIG. 38  
FIG. 39  
FIG. 40  
FIG. 41  
FIG. 42  
FIG. 43  
FIG. 44  
FIG. 45  
FIG. 46  
FIG. 47  
FIG. 48  
FIG. 49  
FIG. 50  
FIG. 51  
FIG. 52  
FIG. 53  
FIG. 54  
FIG. 55  
FIG. 56  
FIG. 57  
FIG. 58  
FIG. 59  
FIG. 60  
FIG. 61  
FIG. 62  
FIG. 63  
FIG. 64  
FIG. 65  
FIG. 66  
FIG. 67  
FIG. 68  
FIG. 69  
FIG. 70  
FIG. 71  
FIG. 72  
FIG. 73  
FIG. 74  
FIG. 75  
FIG. 76  
FIG. 77  
FIG. 78  
FIG. 79  
FIG. 80  
FIG. 81  
FIG. 82  
FIG. 83  
FIG. 84  
FIG. 85  
FIG. 86  
FIG. 87  
FIG. 88  
FIG. 89  
FIG. 90  
FIG. 91  
FIG. 92  
FIG. 93  
FIG. 94  
FIG. 95  
FIG. 96  
FIG. 97  
FIG. 98  
FIG. 99  
FIG. 100  
FIG. 101  
FIG. 102  
FIG. 103  
FIG. 104  
FIG. 105  
FIG. 106  
FIG. 107  
FIG. 108  
FIG. 109  
FIG. 110  
FIG. 111  
FIG. 112  
FIG. 113  
FIG. 114  
FIG. 115  
FIG. 116  
FIG. 117  
FIG. 118  
FIG. 119  
FIG. 120  
FIG. 121  
FIG. 122  
FIG. 123  
FIG. 124  
FIG. 125  
FIG. 126  
FIG. 127  
FIG. 128  
FIG. 129  
FIG. 130  
FIG. 131  
FIG. 132  
FIG. 133  
FIG. 134  
FIG. 135  
FIG. 136  
FIG. 137  
FIG. 138  
FIG. 139  
FIG. 140  
FIG. 141  
FIG. 142  
FIG. 143  
FIG. 144  
FIG. 145  
FIG. 146  
FIG. 147  
FIG. 148  
FIG. 149  
FIG. 150  
FIG. 151  
FIG. 152  
FIG. 153  
FIG. 154  
FIG. 155  
FIG. 156  
FIG. 157  
FIG. 158  
FIG. 159  
FIG. 160  
FIG. 161  
FIG. 162  
FIG. 163  
FIG. 164  
FIG. 165  
FIG. 166  
FIG. 167  
FIG. 168  
FIG. 169  
FIG. 170  
FIG. 171  
FIG. 172  
FIG. 173  
FIG. 174  
FIG. 175  
FIG. 176  
FIG. 177  
FIG. 178  
FIG. 179  
FIG. 180  
FIG. 181  
FIG. 182  
FIG. 183  
FIG. 184  
FIG. 185  
FIG. 186  
FIG. 187  
FIG. 188  
FIG. 189  
FIG. 190  
FIG. 191  
FIG. 192  
FIG. 193  
FIG. 194  
FIG. 195  
FIG. 196  
FIG. 197  
FIG. 198  
FIG. 199  
FIG. 200  
FIG. 201  
FIG. 202  
FIG. 203  
FIG. 204  
FIG. 205  
FIG. 206  
FIG. 207  
FIG. 208  
FIG. 209  
FIG. 210  
FIG. 211  
FIG. 212  
FIG. 213  
FIG. 214  
FIG. 215  
FIG. 216  
FIG. 217  
FIG. 218  
FIG. 219  
FIG. 220  
FIG. 221  
FIG. 222  
FIG. 223  
FIG. 224  
FIG. 225  
FIG. 226  
FIG. 227  
FIG. 228  
FIG. 229  
FIG. 230  
FIG. 231  
FIG. 232  
FIG. 233  
FIG. 234  
FIG. 235  
FIG. 236  
FIG. 237  
FIG. 238  
FIG. 239  
FIG. 240  
FIG. 241  
FIG. 242  
FIG. 243  
FIG. 244  
FIG. 245  
FIG. 246  
FIG. 247  
FIG. 248  
FIG. 249  
FIG. 250  
FIG. 251  
FIG. 252  
FIG. 253  
FIG. 254  
FIG. 255  
FIG. 256  
FIG. 257  
FIG. 258  
FIG. 259  
FIG. 260  
FIG. 261  
FIG. 262  
FIG. 263  
FIG. 264  
FIG. 265  
FIG. 266  
FIG. 267  
FIG. 268  
FIG. 269  
FIG. 270  
FIG. 271  
FIG. 272  
FIG. 273  
FIG. 274  
FIG. 275  
FIG. 276  
FIG. 277  
FIG. 278  
FIG. 279  
FIG. 280  
FIG. 281  
FIG. 282  
FIG. 283  
FIG. 284  
FIG. 285  
FIG. 286  
FIG. 287  
FIG. 288  
FIG. 289  
FIG. 290  
FIG. 291  
FIG. 292  
FIG. 293  
FIG. 294  
FIG. 295  
FIG. 296  
FIG. 297  
FIG. 298  
FIG. 299  
FIG. 300  
FIG. 301  
FIG. 302  
FIG. 303  
FIG. 304  
FIG. 305  
FIG. 306  
FIG. 307  
FIG. 308  
FIG. 309  
FIG. 310  
FIG. 311  
FIG. 312  
FIG. 313  
FIG. 314  
FIG. 315  
FIG. 316  
FIG. 317  
FIG. 318  
FIG. 319  
FIG. 320  
FIG. 321  
FIG. 322  
FIG. 323  
FIG. 324  
FIG. 325  
FIG. 326  
FIG. 327  
FIG. 328  
FIG. 329  
FIG. 330  
FIG. 331  
FIG. 332  
FIG. 333  
FIG. 334  
FIG. 335  
FIG. 336  
FIG. 337  
FIG. 338  
FIG. 339  
FIG. 340  
FIG. 341  
FIG. 342  
FIG. 343  
FIG. 344  
FIG. 345  
FIG. 346  
FIG. 347  
FIG. 348  
FIG. 349  
FIG. 350  
FIG. 351  
FIG. 352  
FIG. 353  
FIG. 354  
FIG. 355  
FIG. 356  
FIG. 357  
FIG. 358  
FIG. 359  
FIG. 360  
FIG. 361  
FIG. 362  
FIG. 363  
FIG. 364  
FIG. 365  
FIG. 366  
FIG. 367  
FIG. 368  
FIG. 369  
FIG. 370  
FIG. 371  
FIG. 372  
FIG. 373  
FIG. 374  
FIG. 375  
FIG. 376  
FIG. 377  
FIG. 378  
FIG. 379  
FIG. 380  
FIG. 381  
FIG. 382  
FIG. 383  
FIG. 384  
FIG. 385  
FIG. 386  
FIG. 387  
FIG. 388  
FIG. 389  
FIG. 390  
FIG. 391  
FIG. 392  
FIG. 393  
FIG. 394  
FIG. 395  
FIG. 396  
FIG. 397  
FIG. 398  
FIG. 399  
FIG. 400  
FIG. 401  
FIG. 402  
FIG. 403  
FIG. 404  
FIG. 405  
FIG. 406  
FIG. 407  
FIG. 408  
FIG. 409  
FIG. 410  
FIG. 411  
FIG. 412  
FIG. 413  
FIG. 414  
FIG. 415  
FIG. 416  
FIG. 417  
FIG. 418  
FIG. 419  
FIG. 420  
FIG. 421  
FIG. 422  
FIG. 423  
FIG. 424  
FIG. 425  
FIG. 426  
FIG. 427  
FIG. 428  
FIG. 429  
FIG. 430  
FIG. 431  
FIG. 432  
FIG. 433  
FIG. 434  
FIG. 435  
FIG. 436  
FIG. 437  
FIG. 438  
FIG. 439  
FIG. 440  
FIG. 441  
FIG. 442  
FIG. 443  
FIG. 444  
FIG. 445  
FIG. 446  
FIG. 447  
FIG. 448  
FIG. 449  
FIG. 450  
FIG. 451  
FIG. 452  
FIG. 453  
FIG. 454  
FIG. 455  
FIG. 456  
FIG. 457  
FIG. 458  
FIG. 459  
FIG. 460  
FIG. 461  
FIG. 462  
FIG. 463  
FIG. 464  
FIG. 465  
FIG. 466  
FIG. 467  
FIG. 468  
FIG. 469  
FIG. 470  
FIG. 471  
FIG. 472  
FIG. 473  
FIG. 474  
FIG. 475  
FIG. 476  
FIG. 477  
FIG. 478  
FIG. 479  
FIG. 480  
FIG. 481  
FIG. 482  
FIG. 483  
FIG. 484  
FIG. 485  
FIG. 486  
FIG. 487  
FIG. 488  
FIG. 489  
FIG. 490  
FIG. 491  
FIG. 492  
FIG. 493  
FIG. 494  
FIG. 495  
FIG. 496  
FIG. 497  
FIG. 498  
FIG. 499  
FIG. 500  
FIG. 501  
FIG. 502  
FIG. 503  
FIG. 504  
FIG. 505  
FIG. 506  
FIG. 507  
FIG. 508  
FIG. 509  
FIG. 510  
FIG. 511  
FIG. 512  
FIG. 513  
FIG. 514  
FIG. 515  
FIG. 516  
FIG. 517  
FIG. 518  
FIG. 519  
FIG. 520  
FIG. 521  
FIG. 522  
FIG. 523  
FIG. 524  
FIG. 525  
FIG. 526  
FIG. 527  
FIG. 528  
FIG. 529  
FIG. 530  
FIG. 531  
FIG. 532  
FIG. 533  
FIG. 534  
FIG. 535  
FIG. 536  
FIG. 537  
FIG. 538  
FIG. 539  
FIG. 540  
FIG. 541  
FIG. 542  
FIG. 543  
FIG. 544  
FIG. 545  
FIG. 546  
FIG. 547  
FIG. 548  
FIG. 549  
FIG. 550  
FIG. 551  
FIG. 552  
FIG. 553  
FIG. 554  
FIG. 555  
FIG. 556  
FIG. 557  
FIG. 558  
FIG. 559  
FIG. 560  
FIG. 561  
FIG. 562  
FIG. 563  
FIG. 564  
FIG. 565  
FIG. 566  
FIG. 567  
FIG. 568  
FIG. 569  
FIG. 570  
FIG. 571  
FIG. 572  
FIG. 573  
FIG. 574  
FIG. 575  
FIG. 576  
FIG. 577  
FIG. 578  
FIG. 579  
FIG. 580  
FIG. 581  
FIG. 582  
FIG. 583  
FIG. 584  
FIG. 585  
FIG. 586  
FIG. 587  
FIG. 588  
FIG. 589  
FIG. 590  
FIG. 591  
FIG. 592  
FIG. 593  
FIG. 594  
FIG. 595  
FIG. 596  
FIG. 597  
FIG. 598  
FIG. 599  
FIG. 600  
FIG. 601  
FIG. 602  
FIG. 603  
FIG. 604  
FIG. 605  
FIG. 606  
FIG. 607  
FIG. 608  
FIG. 609  
FIG. 610  
FIG. 611  
FIG. 612  
FIG. 613  
FIG. 614  
FIG. 615  
FIG. 616  
FIG. 617  
FIG. 618  
FIG. 619  
FIG. 620  
FIG. 621  
FIG. 622  
FIG. 623  
FIG. 624  
FIG. 625  
FIG. 626  
FIG. 627  
FIG. 628  
FIG. 629  
FIG. 630  
FIG. 631  
FIG. 632  
FIG. 633  
FIG. 634  
FIG. 635  
FIG. 636  
FIG. 637  
FIG. 638  
FIG. 639  
FIG. 640  
FIG. 641  
FIG. 642  
FIG. 643  
FIG. 644  
FIG. 645  
FIG. 646  
FIG. 647  
FIG. 648  
FIG. 649  
FIG. 650  
FIG. 651  
FIG. 652  
FIG. 653  
FIG. 654  
FIG. 655  
FIG. 656  
FIG. 657  
FIG. 658  
FIG. 659  
FIG. 660  
FIG. 661  
FIG. 662  
FIG. 663  
FIG. 664  
FIG. 665  
FIG. 666  
FIG. 667  
FIG. 668  
FIG. 669  
FIG. 670  
FIG. 671  
FIG. 672  
FIG. 673  
FIG. 674  
FIG. 675  
FIG. 676  
FIG. 677  
FIG. 678  
FIG. 679  
FIG. 680  
FIG. 681  
FIG. 682  
FIG. 683  
FIG. 684  
FIG. 685  
FIG. 686  
FIG. 687  
FIG. 688  
FIG. 689  
FIG. 690  
FIG. 691  
FIG. 692  
FIG. 693  
FIG. 694  
FIG. 695  
FIG. 696  
FIG. 697  
FIG. 698  
FIG. 699  
FIG. 700  
FIG. 701  
FIG. 702  
FIG. 703  
FIG. 704  
FIG. 705  
FIG. 706  
FIG. 707  
FIG. 708  
FIG. 709  
FIG. 710  
FIG. 711  
FIG. 712  
FIG. 713  
FIG. 714  
FIG. 715  
FIG. 716  
FIG. 717  
FIG. 718  
FIG. 719  
FIG. 720  
FIG. 721  
FIG. 722  
FIG. 723  
FIG. 724  
FIG. 725  
FIG. 726  
FIG. 727  
FIG. 728  
FIG. 729  
FIG. 730  
FIG. 731  
FIG. 732  
FIG. 733  
FIG. 734  
FIG. 735  
FIG. 736  
FIG. 737  
FIG. 738  
FIG. 739  
FIG. 740  
FIG. 741  
FIG. 742  
FIG. 743  
FIG. 744  
FIG. 745  
FIG. 746  
FIG. 747  
FIG. 748  
FIG. 749  
FIG. 750  
FIG. 751  
FIG. 752  
FIG. 753  
FIG. 754  
FIG. 755  
FIG. 756  
FIG. 757  
FIG. 758  
FIG. 759  
FIG. 760  
FIG. 761  
FIG. 762  
FIG. 763  
FIG. 764  
FIG. 765  
FIG. 766  
FIG. 767  
FIG. 768  
FIG. 769  
FIG. 770  
FIG. 771  
FIG. 772  
FIG. 773  
FIG. 774  
FIG. 775  
FIG. 776  
FIG. 777  
FIG. 778  
FIG. 779  
FIG. 780  
FIG. 781  
FIG. 782  
FIG. 783  
FIG. 784  
FIG. 785  
FIG. 786  
FIG. 787  
FIG. 788  
FIG. 789  
FIG. 790  
FIG. 791  
FIG. 792  
FIG. 793  
FIG. 794  
FIG. 795  
FIG. 796  
FIG. 797  
FIG. 798  
FIG. 799  
FIG. 800  
FIG. 801  
FIG. 802  
FIG. 803  
FIG. 804  
FIG. 805  
FIG. 806  
FIG. 807  
FIG. 808  
FIG. 809  
FIG. 810  
FIG. 811  
FIG. 812  
FIG. 813  
FIG. 814  
FIG. 815  
FIG. 816  
FIG. 817  
FIG. 818  
FIG. 819  
FIG. 820  
FIG. 821  
FIG. 822  
FIG. 823  
FIG. 824  
FIG. 825  
FIG. 826  
FIG. 827  
FIG. 828  
FIG. 829  
FIG. 830  
FIG. 831  
FIG. 832  
FIG. 833  
FIG. 834  
FIG. 835  
FIG. 836  
FIG. 837  
FIG. 838  
FIG. 839  
FIG. 840  
FIG. 841  
FIG. 842  
FIG. 843  
FIG. 844  
FIG. 845  
FIG. 846  
FIG. 847  
FIG. 848  
FIG. 849  
FIG. 850  
FIG. 851  
FIG. 852  
FIG. 853  
FIG. 854  
FIG. 855  
FIG. 856  
FIG. 857  
FIG. 858  
FIG. 859  
FIG. 860  
FIG. 861  
FIG. 862  
FIG. 863  
FIG. 864  
FIG. 865  
FIG. 866  
FIG. 867  
FIG. 868  
FIG. 869  
FIG. 870  
FIG. 871  
FIG. 872  
FIG. 873  
FIG. 874  
FIG. 875  
FIG. 876  
FIG. 877  
FIG. 878  
FIG. 879  
FIG. 880  
FIG. 881  
FIG. 882  
FIG. 883  
FIG. 884  
FIG. 885  
FIG. 886  
FIG. 887  
FIG. 888  
FIG. 889  
FIG. 890  
FIG. 891  
FIG. 892  
FIG. 893  
FIG. 894  
FIG. 895  
FIG. 896  
FIG. 897  
FIG. 898  
FIG. 899  
FIG. 900  
FIG. 901  
FIG. 902  
FIG. 903  
FIG. 904  
FIG. 905  
FIG. 906  
FIG. 907  
FIG. 908  
FIG. 909  
FIG. 910  
FIG. 911  
FIG. 912  
FIG. 913  
FIG. 914  
FIG. 915  
FIG. 916  
FIG. 917  
FIG. 918  
FIG. 919  
FIG. 920  
FIG. 921  
FIG. 922  
FIG. 923  
FIG. 924  
FIG. 925  
FIG. 926  
FIG. 927  
FIG. 928  
FIG. 929  
FIG. 930  
FIG. 931  
FIG. 932  
FIG. 933  
FIG. 934  
FIG. 935  
FIG. 936  
FIG. 937  
FIG. 938  
FIG. 939  
FIG. 940  
FIG. 941  
FIG. 942  
FIG. 943  
FIG. 944  
FIG. 945  
FIG. 946  
FIG. 947  
FIG. 948  
FIG. 949  
FIG. 950  
FIG. 951  
FIG. 952  
FIG. 953  
FIG. 954  
FIG. 955  
FIG. 956  
FIG. 957  
FIG. 958  
FIG. 959  
FIG. 960  
FIG. 961  
FIG. 962  
FIG. 963  
FIG. 964  
FIG. 965  
FIG. 966  
FIG. 967  
FIG. 968  
FIG. 969  
FIG. 970  
FIG. 971  
FIG. 972  
FIG. 973  
FIG. 974  
FIG. 975  
FIG. 976  
FIG. 977  
FIG. 978  
FIG. 979  
FIG. 980  
FIG. 981  
FIG. 982  
FIG. 983  
FIG. 984  
FIG. 985  
FIG. 986  
FIG. 987  
FIG. 988  
FIG. 989  
FIG. 990  
FIG. 991  
FIG. 992  
FIG. 993  
FIG. 994  
FIG. 995  
FIG. 996  
FIG. 997  
FIG. 998  
FIG. 999  
FIG. 1000

10       Figures 5 and 6 depict a second embodiment of the present invention. Zippered packages 52, either in a chain 54 as shown in figure 5 or individually as shown in figure 6, are output from an HFFS machine (not shown), or any other type of bag making machine. In the case of figure 5, the package chain 54 is indexed into a slider insertion station 56. At the slider insertion station 56 or at an earlier station, the ends of the zipper 36 on the leading package in the chain 54 are stomped as discussed above. Then, a slider 44 is removed from the slider coil 46 and inserted on to the zipper 36. Finally, a completed package 58 have a slide zipper is cross-cut from the chain by a cutting apparatus (not shown).

15       In the case of figure 6, the packages 52 are individual and not chained together. The individual packages 52 are transported one by one into the slider insertion station 56 by a conveyor belt 60 or the like, where the ends of the zipper 36 on the leading package are stomped (unless the stomping was done during package formation) and a slider 44 is removed from the slider coil 46 and inserted on to the zipper 36 to provide a completed slide-zippered package 58.

20       In accordance with a third embodiment of the present invention, figure 7 shows a

thermoform HFFS machine 62 configured to make slide-zippered packages. As in figure 1, the forming film 12 is indexed off a coil 14 of the same. Downstream of the forming film coil 14 at a forming station 15 the forming film 12 is thermoformed into a chain 13 of box-like bottom portions or trays 16 of what will ultimately be completed packages. Product may then be loaded into the bottom portions 16 at the loading station 17 if desired. Each bottom portion 16 is provided with a lip 64 on one side thereof, as shown in figure 8, which is a cross-sectional view of the chain 13. After optional product loading, the reclosable zipper 36 is indexed off a coil 38 of the same and laid over the lips 64 of the bottom portions 16. The lower zipper flange 42 is then sealed to the lips 64 by a sealing mechanism, such as a heater bar 63, at a sealing station 68. The heater bar 63 is positioned below the lips 64, as shown in figure 7a, which is a cross-sectional view of zipper attachment to the package lips. Also shown in figure 7a is an insulating and guide plate 67 positioned between the zipper flanges. The insulating and guide plate 67 provides a surface for the heater bar to react against and removes any danger of sealing through the zipper flanges, thereby eliminating the need for accurate heat control. The insulating and guide plate 67 also serves to guide and position the zipper onto the package lips to ensure accurate sealing.

A slider 44 is then removed from the slider coil 46 and inserted on to the zipper 36 of the instant bottom portion 16 at an insertion station 70. After slider insertion, the ends of the zipper are stomped. Alternatively, the zipper ends could have been stomped together earlier, either on the machine or pre-stomped prior to winding on the supply coil, and the zipper indexed to the bottom portion. The top film 18 is then indexed off the top film coil 20, laid over the formed bottoms 16 and the attached zipper 36 and sealed to the formed bottoms 16



and the upper flange 40 of the zipper 36 around the perimeter of the package at a second sealing station 72. As discussed above, the seal at the mouth of the package may take the form of a peel seal to provide easy access to the contents of the package. Optionally, the top film 18, if it is long enough, may be heat tacked to the bottom portion 16 over the zipper 36 to provide a tamper evident seal 65, as shown in figure 9. In the final step, the completed packages 48 are cross-cut from the chain at a cutting station 74. If a double chain is used, as shown in figure 8, then the side-by-side packages must also be cut from each other in the machine direction.

When making packages using multiple package chains, it is not necessary that the zippers and sliders be applied to opposite sides 47, 49 of the package chain, as shown in figures 4 and 8. Rather, it is also possible to apply the zippers and sliders to the same sides of the packages. For example, a triple package chain is shown in figures 10 and 11. In this case the top film 18 is pre-perforated so that it can be split into three sections and laid over each of the bottom portions 16. This splitting is achieved by a separator assembly 78 having three L-shaped separator plates 78a, 78b, 78c. As the top film 18 is indexed off its roll 20, the vertical portions of the separator plates 78a, 78b, 78c split the pre-perforated top film 18 into three portions 18a, 18b, 18c and guide the three top film portions as they are laid over their corresponding bottom portions 16. Additionally, the horizontal portions of the separator plates interact with the sealing mechanism to ensure that there is no seal through, eliminating the need for accurate heat control.

As indicated above, the present invention is not limited to thermoform HFFS machines, but may be practiced on any type of HFFS machine and on any type of bag making

machine for that matter. Figure 12 shows how slide-zipped packages can be made on a horizontal form-vertical fill-seal machine (HFVS) 80 in accordance with a fourth embodiment of the present invention.

Package film 82 is paid off a roll 84 of the same. Downstream a pull roller 98 is  
5 provided for driving the film 82 through the machine. A folder plow 86 positioned downstream of the film roll 84 folds the package film 82 about a bottom crease 83 to form opposing package walls 116, 118. Interlocked reclosable zipper 36 is then paid off a roll 38 of the same and fed between the advancing package walls. Sliders 44 are inserted on to the reclosable zipper 36 prior to the folder plow 86 at package width intervals at what will be the  
10 closing end of the zipper by a slider insertion mechanism at the slider insertion station 88. The sliders 44 are supplied from the slider coil 46.

At a first sealing station 90, the zipper flanges 40, 42 are sealed to the opposing package walls. Then at stomping stations 92, the ends of the zipper 36 for a given package are stomped. At a second sealing station 94, the folded film and zipper are cross-sealed to  
15 form discrete packages.

Because the zippers are closed, it is necessary to open the zippers in order to fill the packages. This is achieved at a slider opening station 96, where the slider is held in position as the zipper and film are advanced when the pull rollers 98 are activated. As the zipper moves through the slider, it is opened. Alternatively, the slider itself may be moved. Then,  
20 at a cutting station 100 the individual packages 102 are cut from one another. The separated packages 102 are then taken to the filling station 104 where they are filled. Filling may occur by means of a filling turret 106 or the packages may be filled in-line, both of which

techniques are well-known to those of ordinary skill in the art. After a package is filled, the slider 44 is moved backed to the closing end of the zipper. Finally, a tamper evident 108 seal may optionally be provided above the zipper 36. Completed slide-zippered packages 110 are then output from the machine.

5 A first variation of the fourth embodiment is shown in figure 13. As is clear from figure 13, the sliders are attached downstream of the folder plow 86, rather than upstream of the folder plow 86. Additionally, the sliders 44 are attached to the zippers 36 at their opening ends, rather than at their closing ends as above. Thus, in order to open the zippers for package filling the zippers must be forced open from the outside of the packages, rather than  
10 by using the sliders. This opening action is carried out at an opening station 97 by a suitable mechanism provided for the specific zipper construction. After filling at the filling station 104, the slider is moved to the closing end of the zipper.

A second variation of the fourth embodiment of the present invention is shown in figure 14. Under certain circumstances it may be desirable to eliminate the step of opening  
15 the zipper for filling. This can be done by sealing one zipper flange to one side of the folded film at the first sealing station 90 prior to filling, as shown in figure 15, rather than sealing both flanges to the film as done previously.

As shown in figure 15, one flange 40 of the zipper is sealed to one wall 116 of the folded film 82 a distance below the top 120. The film 82 protrudes above the zipper to form  
20 a pair of opposing ears 122. To ensure that the zipper flanges 40, 42 do not seal to each other or the other side of the package at the first sealing station 90, a J-shaped insulator plate 124 is inserted between the zipper flanges 40, 42 and between the unsealed zipper flange 42 and the

other package wall 118, as shown in figure 15. In addition, one of the seal bars 112 is kept hot and the other 114 is deactivated. Then, at the second sealing station 94, the packages are cross-sealed from the bottom of the film 92 up to but not including the zipper. When it comes time to fill the bag at the filling station 104, the zipper is bent to one side, as shown in figure 16. In this manner, filling may proceed unobstructed, and there is no danger of contaminating the zipper. After filling, the unsealed zipper flange 42 is sealed to the other side of the package and the ears 122 are sealed to each other by a pair of seal bars 126 with a perforation seal and a peel seal above the zipper 36, as shown in figure 17. At the same time the ends of the zipper are cross-sealed together and end stops for the slider are created. The above indicated zipper cross-seals extend below the zipper flanges into the package side seals, but not above and beyond the zipper profiles.

A third variation of the fourth embodiment of the present invention is shown in figure 18. In this variation, the zipper 36 and slider 44 are attached to the bottom 128 of the package, rather than at the top 120. As the film 82 is fed over the folder plow 86, a perforator 130 perforates the film 82 below the slider 44 to form a pair of perforations 132 (alternatively, a single perforation 132a may be provided). The zipper is then sealed to the bottom of the package by sealing the zipper flanges to the film beyond the perforation lines, as shown in figure 19. A peel seal 136 may be provided between the zipper flanges in order to maintain the integrity of the packages.

The packages are completed as discussed above, except that they are filled from the opposing end to which the zipper has been attached. Further, if a bottom gusset is required a V shaped film can be introduced between the package walls 116 and 118 and sealed into

place. During use, the packages are inverted so that the zipper and slider are at the top and the perforated portion 134 is torn away from the package to gain access to the slider.

Thus, in the foregoing manner the object of the present invention is achieved.

Modifications to the above would be obvious to those of ordinary skill in the art, but would  
5 not bring the invention so modified beyond the scope of the appended claims.

105220-0757660